
SANTARO 7.0 BX PCT

7.0 inch Panel Mount HMI based on NXP i.MX6 processor

Flexible, powerful all-rounder for any demanding applications

Panel Mount



AI-ENABLED WITH CLEA

HIGHLIGHTS

- **CPU**: NXP i.MX 6 Family
- **CONNECTIVITY**: 1x 100MbE, up to 2x USB, 2x RS232, RS485, CAN
- **GRAPHICS**: GC320 & GC355 2D accelerator + GC2000 3D accelerator
- **MEMORY**: Soldered on Board DDR3L memory

GOLD PARTNER NXP

yocto PROJECT

MAIN FIELDS OF APPLICATION

Biomedical/ Medical devices · Fitness Equipment · HMI · Industrial Automation · Measuring instruments · Multimedia devices · Point of Sales

FEATURES

Processor	NXP i.MX 6 Family based on ARM® Cortex®-A9 cores : i.MX 6 Quad – Full featured, 4x Cortex®-A9 cores up to 1.0GHz i.MX 6 Dual – Full featured, 4x Cortex®-A9 cores up to 1.0GHz i.MX 6 Single – Full featured, 4x Cortex®-A9 cores up to 1.0GHz
Memory	1 GB 64 bit DDR3L
Graphics	Integrated Graphics, with up to 3 separate HW accelerators for 2D, OpenGL® ES2.0 3D OpenVG™ accelerator HW encoding of MPEG-4, H.263 V2, H.264, MJPEG HW decoding of MPEG-2, VC1, MPEG-4 / XviD, H.263, H.264, DivX
Video Resolution	7.0 inch display, resolution 800 x 480, LED lifetime typ. 40k hours typ. 400 cd/m² brightness P-Cap (Projected Capacitive touch screen), with 3.0mm toughened glass cover, RAL 9005
Mass Storage	eMMC: 4 GB MLC SD slot: 4 bit MMC/SDIO/SD/SDHC
Networking	1x 100MbEthernet
USB	1x USB 2.0 OTG micro-AB 1x USB 2.0 Type-A

Audio	1x speaker (connector), 1 W RMS (8Ω) parallel to internal speaker
Other Interfaces	2x Digital Input, 2x Digital Output
Serial Ports	2x RS-232, RS-485
Power Supply	9 ÷ 32 VDC
Operating System	Yocto
CAN Bus	1x CAN (ISO/DIS 11898)
Operating Temperature*	0°C ÷ +60°C
Dimensions	206.9 x 126.2 x 33.6 mm

*Measured at any point of SECO standard heatspreader for this product, during any and all times (including start-up). Actual temperature will widely depend on application, enclosure and/or environment. Upon customer to consider application-specific cooling solutions for the final system to keep the heatspreader temperature in the range indicated.


Information subject to change. Please visit www.edge.seco.com to find the latest version of this datasheet

SANTARO 7.0 BX PCT

7.0 inch Panel Mount HMI based on NXP i.MX6 processor

BLOCK DIAGRAM

SANTARO 7.0 BX PCT



Information subject to change. Please visit www.edge.seco.com to find the latest version of this datasheet